



Product Service

Attestation of Conformity

No. N8A 097386 0046 Rev. 00

Holder of Certificate: **LEDVANCE GmbH**
Parkring 29-33
85748 Garching
GERMANY

Product: **Power supplies
(LED POWER SUPPLY)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 6814020005101

Date, 2020-06-04

(Taylor Yao)

Page 1 of 4

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 097386 0046 Rev. 00

Model(s): DR DALI-PFM-26/220-240/700;
DR DALI-PFM-44/220-240/1050;
DR DALI-PFM-60/220-240/1A4;
LVED SUP 60/220-240/1A4 DIM;
DR DALI-SUP-45/220-240/24;
LVED SUP 45/220-240/24 DIM;
DR DALI-SUP-80/220-240/24;
LVED SUP 80/220-240/24 DIM;
DR DALI-SUP-150/220-240/24;
LVED SUP 150/220-240/24 DIM

Brand: LEDVANCE



Parameters:

Rated Input Voltage: See below table for details

Rated Frequency: See below table for details

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II (for independent type); SELV

Degree of Protection: IP20 (for independent type)

Method of Installation: See below table for details

Type of Output: See below table for details

ta: See below table for details

tc: See below table for details



Attestation of Conformity

No. N8A 097386 0046 Rev. 00

Model No.	Rated Input Voltage (V)/Rated Frequency (Hz)	Rated Input Current (A) Max.	Output Voltage (VDC)	Irated (mA)	Uout (VDC)	Prated (W)	Value Of ta; tc (°C)	Type of Output	Method of Installation								
DR DALI-PFM-26/220-240/700	220-240VAC; 50/60Hz; 196-245VDC	0.176 (AC); 0.15 (DC)	9-52	150	60	7.8	ta: 50; tc: 85	Constant Current Type	Independent (with endcap); Built-in (without endcap)								
				200		10.4											
				250		13											
				300		15.6											
				350		18.2											
				400		20.8											
				450		23.4											
				500		26											
				9-47.5		26.1											
				9-43.5		26.1											
				9-40		26											
				9-37.5		26.3											
				DR DALI-PFM-44/220-240/1050		220-240VAC; 50/60Hz; 196-245VDC				0.275 (AC); 0.24 (DC)	9-52	700	60	36.4	ta: 50; tc: 90	Constant Current Type	Independent (with endcap); Built-in (without endcap)
750	39																
800	41.6																
850	41.7																
900	44.1																
9-46	43.7																
9-44	44																
9-42	44.1																
DR DALI-PFM-60/220-240/1A4; LVED SUP 60/220-240 /1A4 DIM	220-240VAC; 50/60Hz; 196-245VDC	0.385 (AC); 0.32 (DC)	9-52		700		60	36.4	ta: 50; tc: 90			Constant Current Type		Independent (with endcap); Built-in (without endcap)			
					750			39									
				800	41.6												
				850	44.2												
				900	46.8												
				950	49.4												
				1000	52												
				1050	54.6												
				1100	57.2												
				1150	59.8												
				9-50	60												
				9-48	60												
				9-46	59.8												
				9-44	59.4												
				9-43	60.2												



Product Service

Attestation of Conformity

No. N8A 097386 0046 Rev. 00

Model No.	Rated Input Voltage (V)/Rated Frequency (Hz)	Rated Input Current (A) Max.	Urated (VDC)	Output Current (A)	Prated (W)	Value of ta; tc (°C)	Type of Output	Method of Installation
DR DALI-SUP-45/220-240/24; LVED SUP 45/220-240/24 DIM	220-240VAC; 50/60Hz	0.275	24	1.88	45	ta: 50; tc: 85	Constant Voltage Type	Independent
DR DALI-SUP-80/220-240/24; LVED SUP 80/220-240/24 DIM		0.462	24	3.33	80	ta: 45; tc: 85		
DR DALI-SUP-150/220-240/24; LVED SUP 150/220-240/24 DIM		0.825	24	6.25	150	ta: 45; tc: 85		

Tested according to:

EN 61347-2-13:2014/A1:2017
 EN 61347-1:2015
 EN 62493:2015