


ALGINE 2w1 6W downlight




Power	6 W	Voltage	230 V
Luminous flux*	580 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	110 °
IK	06	Degree of protection (IP)	IP20




See more on dedicated page 



 Declaration of Conformity



 Photometric file



 3D model

Technical data:

Code	SLI037027NW
Power	6 W
Nominal current	48 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	580 lm (120°)
Luminous flux**	580 lm (360°)
Lamp efficacy	97 lm/W
Luminous intensity	220 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	115x35 mm
Mounting hole	?95 mm
Weight	0.15 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	Inside
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux