


NOCTIS LUX 3 10W floodlight




CE

Power	10 W	Voltage	230 V
Luminous flux*	975 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65




See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029052NW_PW
Power	10 W
Nominal current	45 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	975 lm (120°)
Luminous flux**	975 lm (360°)
Lamp efficacy	98 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	90x75x27 mm
Weight	0.159 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux