


NOCTIS LUX 3 10W floodlight



CE

| | | | |
|-----------------|-----------------------|---------------------------|---------------|
| Power | 10 W | Voltage | 230 V |
| Luminous flux* | 1000 lm (120°) | Colour temperature | 6000 K |
| Colour of light | CW | Beam angle | 100 ° |
| IK | 07 | Degree of protection (IP) | IP65 |



See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|-----------------|
| Code | SLI029052CW_PW |
| Power | 10 W |
| Nominal current | 45 mA |
| Voltage | 230 V |
| Energy efficiency class | E |
| Energy consumption | 10 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 1000 lm (120°) |
| Luminous flux** | 1000 lm (360°) |
| Lamp efficacy | 100 lm/W |
| Colour temperature | 6000 K |
| Colour of light | CW |
| Beam angle | 100 ° |
| RA | >70 |
| Uniformity of color SDCM max | 5 |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, GLASS |
| IK | 07 |
| Degree of protection (IP) | IP65 |
| Colour | White |
| Dimension (AxBxC) | 90x75x27 mm |
| Weight | 0.159 kg |
| For use | Outside |
| Assembly method | On the ceiling |
| Application | EXT |
| Made in | PRC |



*applies to the LED source used. **Luminaire luminous flux