

## LED STRIP 30 (4,8)W 12V with cover 5 meter roll



Power	<b>30 (4,8) W</b>	Voltage	<b>12 V</b>
Luminous flux**	<b>2500 (350) lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
Socket	<b>prEXTody</b>	Degree of protection (IP)	<b>IP44</b>



 Declaration of Conformity

Technical data:

Code	WOJ+12211
Power	30 (4,8) W
Nominal current	2500 mA
Voltage	12 V
Energy efficiency class	F
Energy consumption	33 kWh/1000h
Frequency	DC Hz
Power factor	1
Useful luminous flux*	2500 lm (120°)
Luminous flux**	2500 (350) lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	90
Uniformity of color SDCM max	5
Dimmable	+
Working temperature range	-20/+40 °
Lifespan	50000 h
Socket	prEXTody
Degree of protection (IP)	IP44
Dimension (AxBxC)	8X5000 mm
Weight	0,032 kg
For use	Inside/Outside
Application	INT
Made in	PRC
Other	0,5m-400mA, NEEi - F

