


## NOCTIS LUX 2 20W floodlight




CE

Power	<b>20 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1820 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>100 °</b>
Degree of protection (IP)	<b>IP65</b>		




See more on dedicated page 




 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI029042NW
Power	20 W
Nominal current	90 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	1820 lm (120°)
Luminous flux**	1750/1820 lm (360°)
Lamp efficacy	88 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	95x120x25 mm
Weight	0.27 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux