


DURE 3 12W downlight




CE

Power	12 W	Voltage	230 V
Luminous flux*	1500 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	110 °
IK	6	Degree of protection (IP)	IP54




See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI043007NW_PW
Power	12 W
Nominal current	86 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	1500 lm (360°)
Luminous flux**	1100 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC+PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	145x34 mm
Mounting hole	120 mm
Weight	0.11 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



*applies to the LED source used, **Luminaire luminous flux