

## ALGINE ECO 12W downlight



Power	<b>12 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>830 lm (120°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>




 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI036018WW
Power	12 W
Nominal current	60 mA
Voltage	230 V
Energy efficiency class	G
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Useful luminous flux*	830 lm (120°)
Luminous flux**	750 lm (360°)
Lamp efficacy	62 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, STEEL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	170x170x22 (bez zasilacza) mm
Mounting hole	155x155 mm
Weight	0.38 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux