

FIALE II 6W COB 38st 230V NW LED SPOT brushed aluminium ring



CE


Power	<b>6 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>4000 K</b>	Colour of light	<b>Neutral white</b>
Beam angle	<b>38 °</b>	Degree of protection (IP)	<b>IP20</b>



 Declaration of Conformity

**Technical data:**

Code	SLI021030NW
Power	6 W
Nominal current	50 mA
Voltage	230 V
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Luminous flux**	420 lm (360°)
Lamp efficacy	70 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	38 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	SREBRNY
Dimension (AxBxC)	86xH65 mm
Mounting hole	fi 75 mm
Weight	0.208 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux