


ALGINE 2IN1 SURFACE-RECESSED DOWNLIGHT 18W 1820LM WW 230V IP20 ROUND



CE

| | | | |
|-----------------|-----------------------|---------------------------|---------------|
| Power | 18 W | Voltage | 230 V |
| Luminous flux* | 2200 lm (360°) | Colour temperature | 3000 K |
| Colour of light | WW | Beam angle | 110 ° |
| IK | 06 | Degree of protection (IP) | IP20 |



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|----------------|
| Code | SLI037029WW_PW |
| Power | 18 W |
| Nominal current | 140 mA |
| Voltage | 230 V |
| Energy efficiency class | E |
| Energy consumption | 18 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | Yes |
| Power factor | 0.5 |
| Useful luminous flux* | 2200 lm (360°) |
| Luminous flux** | 1750 lm (360°) |
| Lamp efficacy | 122 lm/W |
| Luminous intensity | 670 cd |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 110 ° |
| RA | >80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 17000 h |
| Housing material | PLASTIC |
| IK | 06 |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 223x35 mm |
| Mounting hole | o200 mm |
| Weight | 0.37 kg |
| For use | Inside |
| Assembly method | NATYNK/PODTYNK |
| Application | Inside |
| Made in | PRC |



*applies to the LED source used. **Luminaire luminous flux