


NOCTIS LUX 2 20W floodlight with motion sensor



CE

Power	20 W	Voltage	230 V
Luminous flux*	1850 lm (120°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	100 °
Degree of protection (IP)	IP44		



See more on dedicated page 




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029042CW_CZUJNIK
Power	20 W
Nominal current	100 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	1850 lm (120°)
Luminous flux**	1800/1850 lm (360°)
Lamp efficacy	90 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, GLASS
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	158x121x25 mm
Weight	0.3 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux

Motion sensor PIR (sensor regulated, range: 2-10 m., operating time: 10 s. - 7 m., ambient light: 3 - 2000 LUX)