


## ALGINE 12W CCT downlight SPECTRUM SMART




Power	<b>12 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1150 lm (360°)</b>	Colour temperature	<b>3000-6500 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>



 User manual



 Declaration of Conformity




 Photometric file



**Technical data:**

Code	SLI038016CCT
Power	12 W
Nominal current	110 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	1150 lm (360°)
Luminous flux**	1150 lm (360°)
Lamp efficacy	96 lm/W
Colour temperature	3000-6500 K
Colour of light	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC, STEEL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	162x35 mm
Mounting hole	ø155 mm
Weight	0.24 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*applies to the LED source used, \*\*Luminaire luminous flux