


NOCTIS LUX 2 30W floodlight with motion sensor



CE

| | | | |
|---------------------------|-----------------------|--------------------|---------------|
| Power | 30 W | Voltage | 230 V |
| Luminous flux* | 2750 lm (120°) | Colour temperature | 4000 K |
| Colour of light | Neutral white | Beam angle | 100 ° |
| Degree of protection (IP) | IP44 | | |



See more on dedicated page 




 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|--------------------------|
| Code | SLI029043NW_CZUJNIK |
| Power | 30 W |
| Nominal current | 130 mA |
| Voltage | 230 V |
| Energy efficiency class | F |
| Energy consumption | 30 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 2750 lm (120°) |
| Luminous flux** | 2650/2750 lm (360°) |
| Lamp efficacy | 88 lm/W |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 100 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, PLASTIC, GLASS |
| Degree of protection (IP) | IP44 |
| Colour | White |
| Dimension (AxBxC) | 188x160x28 mm |
| Weight | 0.5 kg |
| For use | Inside/Outside |
| Assembly method | On the ceiling |
| Application | INT/EXT |
| Made in | PRC |



*applies to the LED source used. **Luminaire luminous flux

Motion sensor PIR (sensor regulated, range: 2-10 m., operating time: 10 s. - 7 m., ambient light: 3 - 2000 LUX)