


ALGINE 22W CCT downlight SPECTRUM SMART




Power	22 W	Voltage	230 V
Luminous flux*	2000 lm (120°)	Colour temperature	3000-6500 K
Colour of light	CCT	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20



 User manual



 Declaration of Conformity




 Photometric file



Technical data:

Code	SLI038020CCT
Power	22 W
Nominal current	180 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	22 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	2000 lm (120°)
Luminous flux**	2000 lm (360°)
Lamp efficacy	91 lm/W
Colour temperature	3000-6500 K
Colour of light	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC, STEEL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	215x215x38 mm
Mounting hole	205X205 mm
Weight	0.41 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



*applies to the LED source used, **Luminaire luminous flux