


ALGINE BACKLIGHT 40W led panel




CE

Power	40 W	Voltage	230 V
Luminous flux*	4800 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
Degree of protection (IP)	IP20		



See more on dedicated page 




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI035057CW_PW
Power	40 W
Nominal current	177 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4800 lm (360°)
Luminous flux**	3600 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	Aluminum/Steel/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x25 mm
Weight	1.29 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	INT
Made in	PRC



*applies to the LED source used, **Luminaire luminous flux