

ALGINE BACKLIGHT DRIVER 40W led panel



CE

Power	40 W	Voltage	230 V
Luminous flux*	5500 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
Degree of protection (IP)	IP20		



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI035056NW_PW
Power	40 W
Nominal current	186 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	5500 lm (360°)
Luminous flux**	4800 lm (360°)
Lamp efficacy	138 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x26 mm
Mounting hole	575x575mm mm
Weight	1.42 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux