


## NOCTIS LUX 2 100W floodlight




CE

Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8530 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Degree of protection (IP)	<b>IP65</b>



See more on dedicated page 



 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI029035CW
Power	100 W
Nominal current	410 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	8530 lm (120°)
Luminous flux**	8300/8530 lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	270x210x35 mm
Weight	1.25 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux