


NOCTIS LUX 2 100W floodlight




CE

Power	100 W	Voltage	230 V
Luminous flux*	8510 lm (120°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65




See more on dedicated page 





 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029035WW
Power	100 W
Nominal current	410 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	8510 lm (120°)
Luminous flux**	8200/8510 lm (360°)
Lamp efficacy	81 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	270x210x35 mm
Weight	1.25 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux