


ALGINE LED 230V 45W 100LM/W IP20 600X600MM WW CEILING PANEL-5Y WARRANTY



CE

Power	45 W	Voltage	230 V
Luminous flux*	5850 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20




 User manual



 Declaration of Conformity

Technical data:

Code	SLI035037WW_PW
Power	45 W
Nominal current	200 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	5850 lm (360°)
Luminous flux**	4400 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	3
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x10 mm
Mounting hole	575x575 mm
Weight	2.09 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC
Other	L80B50 50000h MTBF 80000h



*applies to the LED source used. **Luminaire luminous flux