


ALGINE LED 230V 45W 100LM/W IP20 300X1200MM NW CEILING PANEL-5Y WARRANTY



CE

| | | | |
|-----------------|-----------------------|---------------------------|---------------|
| Power | 45 W | Voltage | 230 V |
| Luminous flux* | 5900 lm (360°) | Colour temperature | 4000 K |
| Colour of light | Neutral white | Beam angle | 120 ° |
| IK | 06 | Degree of protection (IP) | IP20 |



 User manual



 Declaration of Conformity

Technical data:

| | |
|------------------------------|-----------------------------------|
| Code | SLI035041NW_PW |
| Power | 45 W |
| Nominal current | 190 mA |
| Voltage | 230 V |
| Energy efficiency class | E |
| Energy consumption | 45 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 5900 lm (360°) |
| Luminous flux** | 4500 lm (360°) |
| Lamp efficacy | 100 lm/W |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 120 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum, PLASTIC |
| IK | 06 |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 295x1195x10 mm |
| Mounting hole | 275x1175 mm |
| Weight | 1.8 kg |
| For use | Inside |
| Assembly method | Recessed/On the ceiling/Suspended |
| Application | INT |
| Made in | PRC |



*applies to the LED source used. **Luminaire luminous flux