


ALGINE PREMIUM 30W led panel




CE

Power	30 W	Voltage	230 V
Luminous flux*	4400 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20




See more on dedicated page 




 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI035049NW
Power	30 W
Nominal current	135 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	4400 lm (360°)
Luminous flux**	3800 lm (360°)
Lamp efficacy	146 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x12 mm
Mounting hole	575x575 mm
Weight	2.8 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux