


NOCTIS MAX 150W floodlight




CE

Power	150 W	Voltage	230 V
Luminous flux*	14000 lm (120°)	Colour temperature	6500 K
Colour of light	CW	Beam angle	85 °
IK	08	Degree of protection (IP)	IP65



See more on dedicated page 



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029058CW_PW
Power	150 W
Nominal current	655 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	14000 lm (120°)
Luminous flux**	14000 lm (360°)
Lamp efficacy	93 lm/W
Luminous intensity	7800 cd
Colour temperature	6500 K
Colour of light	CW
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	360x262x30 mm
Weight	1.525 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux