

## ZOSMA 3



Power	<b>19 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>3000 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>40 °</b>	Degree of protection (IP)	<b>IP20</b>



 Declaration of Conformity



 Photometric file

CEL37PRO1983040W

**Technical data:**

Code	WOJP00814
Power	19 W
Nominal current	90.9 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	19 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	2660 lm (360°)
Luminous flux**	2090 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	40 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	169x139 mm
Weight	0.93 kg
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux