


ALGINE LINE 44W led panel




CE

Power	44 W	Voltage	230 V
Luminous flux*	5700 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	70 °
UGR	<16	IK	06




See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI035050NW_PW
Power	44 W
Nominal current	200 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	44 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	PHILIPS
Power factor	0,9
Useful luminous flux*	5700 lm (360°)
Luminous flux**	5300 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	70 °
UGR	<16
RA	>80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	STAL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	597x597x40 mm
Mounting hole	565X565 mm
Weight	2.8 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux