

MONA 2



CE

Power **27 W**

Voltage **230 V**

Colour temperature **3000 K**

Colour of light **WW**

Beam angle **36 °**

Degree of protection (IP) **IP20**



 Declaration of Conformity



 Photometric file



 3D model

CEL41PR02793036W

Technical data:

Code	WOJP02474
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TCI
Power factor	0.93
Useful luminous flux*	3105 lm (360°)
Luminous flux**	2700 lm (360°)
Lamp efficacy	115 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	36 °
RA	90
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	142x118 mm
Mounting hole	Ø110 mm
Weight	0.82 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



*applies to the LED source used. **Luminaire luminous flux