

CEL MIRYDA ROUND 830 19W 230V 40ST WHITE



---

|                    |               |                           |              |
|--------------------|---------------|---------------------------|--------------|
| Power              | <b>19 W</b>   | Voltage                   | <b>230 V</b> |
| Colour temperature | <b>3000 K</b> | Colour of light           | <b>WW</b>    |
| Beam angle         | <b>40 °</b>   | Degree of protection (IP) | <b>IP20</b>  |

---

CEL45PRO1983040W

Technical data:

|                              |                |
|------------------------------|----------------|
| Code                         | WOJP02892      |
| Power                        | 19 W           |
| Nominal current              | 90.9 mA        |
| Voltage                      | 230 V          |
| Energy efficiency class      | E              |
| Energy consumption           | 19 kWh/1000h   |
| Frequency                    | 50HZ Hz        |
| Protection class             | II             |
| Power supply included        | +              |
| Manufacturer of power supply | TCI            |
| Power factor                 | 0.93           |
| Useful luminous flux*        | 2660 lm (360°) |
| Luminous flux**              | 1995 lm (360°) |
| Lamp efficacy                | 140 lm/W       |
| Colour temperature           | 3000 K         |
| Colour of light              | WW             |
| Beam angle                   | 40 °           |
| RA                           | 80             |
| Light source included        | +              |
| Producer of LED diodes       | CREE           |
| Uniformity of color SDCM max | 3              |
| Dimmable                     | OPC            |
| Working temperature range    | -20/+40 °      |
| Lifespan                     | 50000 h        |
| Housing material             | Aluminum       |
| Degree of protection (IP)    | IP20           |
| Colour                       | White          |
| Dimension (AxBxC)            | 180x110 mm     |
| Mounting hole                | Ø160 mm        |
| Weight                       | 1.11 kg        |
| For use                      | Inside         |
| Assembly method              | Recessed       |
| Application                  | Inside         |
| Made in                      | PL             |



\*applies to the LED source used. \*\*Luminaire luminous flux