

CEL MIRYDA ROUND 840 27W 230V 24ST WHITE







Power 27 W

Colour temperature 4000 K

Beam angle 24°

Voltage 230 V

Colour of light

Neutral white

Degree of protection (IP)

IP20

CEL45PR02784024W



Technical data:

Code WOJP02888

Power 27 W

Nominal current 129.1 mA

Voltage 230 V

Energy efficiency class **D**

Energy consumption 27 kWh/1000h

Frequency 50HZ Hz

Protection class

Power supply included +

Manufacturer of power supply TCI

Power factor 0.93

Useful luminous flux* 3780 lm (360°)

Luminous flux** 2835 lm (360°)

Lamp efficacy 140 lm/W

Colour temperature 4000 K

Colour of light Neutral white

Beam angle 24°

RA **80**

Light source included +

Producer of LED diodes CREE

Uniformity of color SDCM max 3

Dimmable OPC

Working temperature range -20/+40 °

Lifespan 50000 h

Housing material Aluminum

Degree of protection (IP) IP20

Colour White

Dimension (AxBxC) 180x110 mm

Mounting hole 0160 mm

Weight 1.11 kg

For use Inside

FOLUSE IIIZIUE

Assembly method Recessed

Application Inside

Made in PL









^{*}applies to the LED source used. **Luminaire luminous flux