

## CEL MIRYDA ROUND 840 27W 230V 12ST WHITE



Power	27 W	Voltage	230 V
Colour temperature	4000 K	Colour of light	Neutral white
Beam angle	12 °	Degree of protection (IP)	IP20

CEL45PR02784012W

## LED PRO LUMINAIRE



[m]

**D**-

1

ON

OFF 30000

## Technical data:

W0JP02887 27 W 129.1 mA 230 V D 27 kWh/1000h 50HZ Hz II + TCI 0.93 3780 Im (360°) 2970 Im (360°) 2970 Im (360°) 2970 Im (360°) 140 Im/W 4000 K Neutral white 12 ° 80 + CREE 3 0PC -20/+40 ° 50000 h Aluminum IP20 White 180x110 mm 0160 mm 1.11 kg	Code Power Nominal current Voltage Energy efficiency class Energy consumption Frequency Protection class Power supply included Manufacturer of power supply Power factor Power factor Useful luminous flux** Luminous flux** Lamp efficacy Colour temperature Colour of light Beam angle RA Light source included Producer of LED diodes Uniformity of color SDCM max Dimmable Uniformity of color SDCM max Lifespan Lifespan Housing material Degree of protection (IP) Colour
0160 mm	Mounting hole

years warranty

\*applies to the LED source used. \*\*Luminaire luminous flux