

CEL MIRYDA ROUND 830 27W 230V 40ST WHITE



---

Power	<b>27 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>3000 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>40 °</b>	Degree of protection (IP)	<b>IP20</b>

---

CEL45PR02783040W

**Technical data:**

Code	WOJP02886
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TCI
Power factor	0.93
Useful luminous flux*	3510 lm (360°)
Luminous flux**	2835 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	40 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	180x110 mm
Mounting hole	Ø160 mm
Weight	1.11 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux