

MONA 3



CE

Power **35 W**

Voltage **230 V**

Colour temperature **3000 K**

Colour of light **WW**

Beam angle **38 °**

Degree of protection (IP) **IP20**



 Photometric file



 3D model

CEL42PR03593038W

Technical data:

Code	WOJP02485
Power	35 W
Nominal current	167.4 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	35 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	3850 lm (360°)
Luminous flux**	3500 lm (360°)
Lamp efficacy	110 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	38 °
RA	90
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	180x130 mm
Mounting hole	Ø145 mm
Weight	1.11 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



*applies to the LED source used. **Luminaire luminous flux