

GEMINA 2



CE

Power **27 W**

Voltage **230 V**

Colour temperature **4000 K**

Colour of light **Neutral white**

Beam angle **60 °**

Degree of protection (IP) **IP20**



 Declaration of Conformity



 Photometric file

MDR46PRO2784060W

Technical data:

Code	WOJP03533
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	TCI
Power factor	0.93
Useful luminous flux*	3780 lm (360°)
Luminous flux**	2970 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	99 x 125 x 167 mm
Weight	1.11 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL



*applies to the LED source used. **Luminaire luminous flux