


NOCTIS MAX 200W floodlight




CE

Power	200 W	Voltage	230 V
Luminous flux*	18000 lm (120°)	Colour temperature	6500 K
Colour of light	CW	Beam angle	85 °
IK	10	Degree of protection (IP)	IP65




See more on dedicated page 



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029057CW_PW
Power	200 W
Nominal current	850 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	18000 lm (120°)
Luminous flux**	18000 lm (360°)
Lamp efficacy	90 lm/W
Luminous intensity	10500 cd
Colour temperature	6500 K
Colour of light	CW
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	10
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	410x290x30 mm
Weight	2 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux