

## ALLDAY 2



CE

Power **30 W**

Voltage **230 V**


Colour temperature **4000 K**

Colour of light **Neutral white**


Beam angle **110 °**

Degree of protection (IP) **IP20**



 Declaration of Conformity



 Photometric file

ALD2PRO308400PW

**Technical data:**

Code	WOJP01017
Power	30 W
Nominal current	167.4 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0,93
Useful luminous flux*	4350 lm (360°)
Luminous flux**	2800 lm (360°)
Lamp efficacy	145 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	80
Light source included	+
Producer of LED diodes	SPECTRUM
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	44x1150x35 mm
Mounting hole	1140x33,5 mm
Weight	2,52 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux