


## STREETOS 100W park/street lamp




CE

Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>14600 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>130/80 °</b>
IK	<b>9</b>	Degree of protection (IP)	<b>IP66</b>




See more on dedicated page 




 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI027015NW_PW
Power	100 W
Nominal current	430 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	14600 lm (360°)
Luminous flux**	14000 lm (360°)
Lamp efficacy	146 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	130/80 °
RA	70
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	9
Degree of protection (IP)	IP66
Colour	Gray
Dimension (AxBxC)	536x166x77 mm
Mounting hole	60 mm
Weight	1.75 kg
For use	Outside
Assembly method	On a pole
Application	EXT
Made in	PRC
Other	100-265V



\*applies to the LED source used. \*\*Luminaire luminous flux