

## ALLDAY 3 ONE SIDE



---

Power	<b>35 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>4000 K</b>	Colour of light	<b>Neutral white</b>
Beam angle	<b>110 °</b>	Degree of protection (IP)	<b>IP20</b>

---



 Declaration of Conformity





 Photometric file

ALD3PRO358400PW

**Technical data:**

Code	WOJP01107
Power	35 W
Nominal current	167.4 mA
Voltage	230 V
Energy consumption	35 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Luminous flux**	2800 lm (360°)
Lamp efficacy	80 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	80
Light source included	+
Producer of LED diodes	SPECTRUM
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	37x1140x100 mm
Weight	2.52 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux