

PESO 2




---

Power	<b>38 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>3000 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>24 °</b>	Degree of protection (IP)	<b>IP20</b>

---



 Photometric file

MDD11PR02\*1983024W

**Technical data:**

Code	WOJP03304
Power	38 W
Nominal current	181.7 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	38 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	5320 lm (360°)
Luminous flux**	3420 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	24 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	82x280x100 mm
Mounting hole	272x92 mm
Weight	1.59 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux