


ALLDAY 5 LINE



| | | | |
|--------------------|---------------|---------------------------|--------------|
| Power | 55 W | Voltage | 230 V |
| Colour temperature | 3000 K | Colour of light | WW |
| Beam angle | 75 ° | Degree of protection (IP) | IP20 |



 Declaration of Conformity



 Photometric file

ALD5PRO55830SMW

Technical data:

| | |
|------------------------------|--------------------------|
| Code | WOJP01211 |
| Power | 55 W |
| Nominal current | 263 mA |
| Voltage | 230 V |
| Energy consumption | 60 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Manufacturer of power supply | TRIDONIC |
| Power factor | 0.93 |
| Luminous flux** | 6325 lm (360°) |
| Lamp efficacy | 115 lm/W |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 75 ° |
| RA | 80 |
| Light source included | + |
| Producer of LED diodes | SPECTRUM |
| Uniformity of color SDCM max | 3 |
| Dimmable | OPC |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 37x1700x100 mm |
| Weight | 3.24 kg |
| For use | Inside |
| Assembly method | On the ceiling/Suspended |
| Application | Inside |
| Made in | PL |



*applies to the LED source used. **Luminaire luminous flux