

ALLDAY 7 ASYMETRIC



Power **55 W**

Voltage **230 V**


Colour temperature **3000 K**

Colour of light **WW**


Beam angle **75 °**

Degree of protection (IP) **IP20**



 Declaration of Conformity



 Photometric file

ALD7PR055830SMB

Technical data:

Code	WOJP03428
Power	55 W
Nominal current	263 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	55 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0,93
Useful luminous flux*	8250 lm (360°)
Luminous flux**	3300 lm (360°)
Lamp efficacy	150 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	75 °
RA	80
Light source included	+
Producer of LED diodes	OSRAM
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	37x1145x115 mm
Weight	2.52 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Application	Inside
Made in	PL



*applies to the LED source used. **Luminaire luminous flux