

MDR FERINA 830 27W 230V 24ST WHITE



---

|                    |               |                           |              |
|--------------------|---------------|---------------------------|--------------|
| Power              | <b>27 W</b>   | Voltage                   | <b>230 V</b> |
| Colour temperature | <b>3000 K</b> | Colour of light           | <b>WW</b>    |
| Beam angle         | <b>24 °</b>   | Degree of protection (IP) | <b>IP20</b>  |

---



 Declaration of Conformity



 Photometric file

MDR38PRO2783024W

Technical data:

|                              |                     |
|------------------------------|---------------------|
| Code                         | WOJP00403           |
| Power                        | 27 W                |
| Nominal current              | 129.1 mA            |
| Voltage                      | 230 V               |
| Energy efficiency class      | E                   |
| Energy consumption           | 27 kWh/1000h        |
| Frequency                    | 50HZ Hz             |
| Protection class             | I                   |
| Power supply included        | +                   |
| Manufacturer of power supply | TCI                 |
| Power factor                 | 0.93                |
| Useful luminous flux*        | 3510 lm (360°)      |
| Luminous flux**              | 2970 lm (360°)      |
| Lamp efficacy                | 130 lm/W            |
| Colour temperature           | 3000 K              |
| Colour of light              | WW                  |
| Beam angle                   | 24 °                |
| RA                           | 80                  |
| Light source included        | +                   |
| Producer of LED diodes       | CREE                |
| Uniformity of color SDCM max | 3                   |
| Working temperature range    | -20/+40 °           |
| Lifespan                     | 50000 h             |
| Housing material             | Aluminum            |
| Degree of protection (IP)    | IP20                |
| Colour                       | White               |
| Dimension (AxBxC)            | 130x220x245 mm      |
| Weight                       | 2.19 kg             |
| For use                      | Inside              |
| Assembly method              | On 3-circuit system |
| Application                  | Inside              |
| Made in                      | PL                  |



\*applies to the LED source used. \*\*Luminaire luminous flux