


ALGINE 2IN1 SURFACE-RECESSED DOWNLIGHT 18W 1900LM NW 230V IP20 ROUND



CE

Power	18 W	Voltage	230 V
Luminous flux*	2200 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	110 °
IK	06	Degree of protection (IP)	IP20



 Declaration of Conformity

Technical data:

Code	SLI037029NW_PW
Power	18 W
Nominal current	140 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	2200 lm (360°)
Luminous flux**	1750 lm (360°)
Lamp efficacy	122 lm/W
Luminous intensity	670 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	223x35 mm
Mounting hole	o200 mm
Weight	0.37 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	Inside
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux