

Product Environmental Profile

Valena™ Life One-way switch - 10 AX - 250V - White



LEGRAND'S ENVIRONMENTAL COMMITMENTS

• **Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

• **Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.

• **Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

Function	Establish, support and interrupt for 20 years rated currents in normal conditions of circuit characterized by a 250 V low voltage with rated load not exceeding 10A.		
Reference Product			
	Cat.No 7 520 01 mechanism	Cat.No 7 550 00 rocker	Cat.No 7 540 01 plate
One-way switch Valena Life - 10 AX 250 V~.			

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



PRODUCTS CONCERNED

The environmental data is representative of the following products:

Catalogue Numbers								
One way switch mechanism only	Two way switch mechanism only	One way switch mechanism + rocker	Two way switch mechanism + rocker	1 Gang plate	2 Gang plate	3 Gang plate	4 Gang plate	5 Gang plate
• 7 520 01	• 7 520 06	• 7 521 01 • 7 522 01 • 7 523 01	• 7 521 06 • 7 522 06 • 7 523 06	• 7 540 91 • 7 541 31 • 7 540 41 • 7 540 81 • 7 540 71 • 7 540 01	• 7 540 92 • 7 541 32 • 7 540 42 • 7 540 82 • 7 540 72 • 7 540 02	• 7 540 93 • 7 541 33 • 7 540 43 • 7 540 83 • 7 540 73 • 7 540 03	• 7 540 94 • 7 541 34 • 7 540 44 • 7 540 84 • 7 540 74 • 7 540 04	• 7 540 95 • 7 541 35 • 7 540 45 • 7 540 85 • 7 540 75 • 7 540 05

Product Environmental Profile

Valena™ Life One-way switch - 10 AX - 250V - White



■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU amended by delegated directive (EU) 2015/863, and its amendment 2017/2102/EU.

Total weight of Reference Product	134 g (all packaging included)				
Plastics as % of weight		Metals as % of weight		Other as % of weight	
PC	22.7 %	Steel	24.2 %		
ABS	11.7 %	Copper alloys	1.1 %		
PS	< 0.1 %	Silver alloys	< 0.1 %		
		Other metal	< 0.1 %		
Packaging as % of weight					
PP	1.8 %			Wood	18.7 %
PET	1.8 %			Paper	17.9 %
PE	0.1 %				
Total plastics	38.1 %	Total metals	25.3 %	Total others	36.6 %

Estimated recycled material content: 20 % by mass.



■ MANUFACTURE

This Reference Product comes from a site that has received ISO14001 certification.



■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 1405 km by road from our warehouse to the local point of distribution into the market in Europe.

Packaging is compliant with European directive 2004/12/EU concerning packaging and packaging waste. At their end of life, its recyclability rate is 88 % (in % of packaging weight).



■ INSTALLATION

For the installation of the product, only standard tools are needed.



■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

Product Environmental Profile

Valena™ Life One-way switch - 10 AX - 250V - White



END OF LIFE

The product end of life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse. This product falls within the scope of the WEEE directive (2012/19/EU). Therefore it must be processed through local WEEE recycling/recovery channels.

• **Extended producer responsibility:**

The sale of this product is subject to a contribution to eco-organisations in each country responsible for managing end of life products in the field of application of the European Waste Electronic and Electrical Equipment Directive.

• **Recyclability rate:**

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 94 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 33 %
- metal materials (excluding packaging) : 25 %
- packaging (all types of materials) : 36 %



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle : manufacturing, distribution, installation, use and end of life. It is representative from products marketed and used in Europe.

For each phase, the following modelling elements were taken in account:

Manufacture	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
Distribution	Transport between the last Group distribution centre and an average delivery point in the sales area.
Installation	The end of life of the packaging.
Use	<ul style="list-style-type: none"> • Product category: PSR0005-ed2-2016 03 29 - § 3.5 Switches. • Use scenario: non-continuous operation for 20 years at 50% of rated load, during 30% of the time. This modelling duration does not constitute a minimum durability requirement. • Energy model: Electricity Mix; Europe 27 - 2008.
End of life	The default end of life scenario maximizing the environmental impacts.
Software and database used	EIME & database CODDE-2018-11

Product Environmental Profile

Valena™ Life
One-way switch - 10 AX - 250V - White



SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
	Value	Unit	Value	%	Value	%	Value	%	Value	%	Value	%
Global warming	3.59E+00	kgCO₂ eq.	5.10E-01	14 %	9.36E-03	< 1 %	3.33E-03	< 1 %	3.06E+00	85 %	7.70E-03	< 1 %
Ozone depletion	2.20E-07	kgCFC-11 eq.	2.06E-08	9 %	1.90E-11	< 1 %	2.80E-11	< 1 %	1.99E-07	91 %	1.55E-10	< 1 %
Acidification of soils and water	1.4E-02	kgSO₂ eq.	1.20E-03	9 %	4.21E-05	< 1 %	1.52E-05	< 1 %	1.28E-02	91 %	3.02E-05	< 1 %
Water eutrophication	2.51E-03	kg(PO₄)³⁻ eq.	1.68E-03	67 %	9.67E-06	< 1 %	1.18E-05	< 1 %	7.70E-04	31 %	3.94E-05	2 %
Photochemical ozone formation	8.28E-04	kgC₂H₄ eq.	1.20E-04	15 %	2.99E-06	< 1 %	1.09E-06	< 1 %	7.01E-04	85 %	2.33E-06	< 1 %
Depletion of abiotic resources - elements	8.59E-05	kgSb eq.	8.56E-05	100 %	3.75E-10	< 1 %	1.53E-10	< 1 %	2.66E-07	< 1 %	4.47E-10	< 1 %
Total use of primary energy	7.64E+01	MJ	1.51E+01	20 %	1.32E-01	< 1 %	4.46E-02	< 1 %	6.11E+01	80 %	8.74E-02	< 1 %
Net use of fresh water	1.11E+01	m³	4.24E-02	< 1 %	8.38E-07	< 1 %	1.10E-06	< 1 %	1.11E+01	100 %	5.41E-06	< 1 %
Depletion of abiotic resources - fossil fuels	4.17E+01	MJ	6.69E+00	16 %	1.32E-01	< 1 %	4.32E-02	< 1 %	3.47E+01	83 %	8.04E-02	< 1 %
Water pollution	2.59E+02	m³	1.30E+02	50 %	1.54E+00	< 1 %	5.03E-01	< 1 %	1.26E+02	49 %	9.34E-01	< 1 %
Air pollution	1.86E+02	m³	5.28E+01	28 %	3.84E-01	< 1 %	3.10E-01	< 1 %	1.32E+02	71 %	7.77E-01	< 1 %

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

Product Environmental Profile

Valena™ Life One-way switch - 10 AX - 250V - White



The environmental impacts refer to a configuration composed by a switch mechanism, a cover and a plate.

To obtain the environmental impacts for each phase of the lifecycle for a 2 way switch configuration, multiply those of the Reference Product by the following coefficients :

	Total LCA	Manufacturing	Distribution	Installation	Use	End of life
Acidification of soil and water	0.8	1.0	1.0	1.0	0.8	1.0
Depletion of abiotic resources - elements	1.1	1.1				
Depletion of abiotic resources - fossil fuels	0.8	1.0				
Air pollution	0.9	1.2				
Water eutrophication	0.9	1.0				
Global warming	0.8	1.0				
Ozon depletion	0.8	1.1				
Photochemical ozon creation	0.8	1.0				
Water pollution	0.9	1.0				
Total use of primary energy	0.8	1.0				
Net use of fresh water	0.8	1.1				

Moreover, for a multi-gang configuration, the described environmental impacts of the 1 Way and 2 Way Switches have to be multiplied by the number of installed products.

Registration number: LGRP-01286-V01.01-EN	Drafting rules: PEP-PCR-ed3-EN-2015 04 02 Supplemented by PSR-0005-ed2-2016 03 29
Verifier accreditation N°: VH23	Information and reference documents: www.pep-ecopassport.org
Date of issue: 10-2021	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
PEP are compliant with XP C08-100-1 : 2016 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804: 2012 + A1 : 2013	

