



### LEGRAND'S ENVIRONMENTAL COMMITMENTS

• **Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).

• **Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.


• **Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



### REFERENCE PRODUCT

<p><b>Function</b></p>	<p>Accommodate and protect the wiring along 1 meter for a reference service life of 20 years. The EUROQUINT 60 x 110mm distribution trunking system with cross-section 5482 mm<sup>2</sup> includes the profile and accessories that are representative of standard use.</p>
<p><b>Reference Product</b></p>	 <p>canal Euroquint 60 x 110</p> <p>Cat.Nos 6 101 60 - 6 101 64 - 6 101 62 - 6 101 66 - 6 101 65</p> <p>EUROQUINT 60 x 110 mm distribution trunking system.</p>

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



### PRODUCTS CONCERNED

The environmental data is representative of the following products:

<p><b>Catalogue Numbers</b></p>
<p>The full EUROQUINT distribution trunking range, as presented in all relevant catalogues (25 x 40 mm to 60 x 200 mm) - details available on request from customer service team.</p>



### ■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU.

<b>Total weight of Reference Product</b>		1460 g (with unit packaging)			
Plastics as % of weight		Metals as % of weight		Other as % of weight	
PVC	83.3 %	Steel	< 0.1 %		
ABS	2.8 %				
PP	< 0.1 %				
PE	< 0.1 %				
				Packaging as % of weight	
				Wood (packaging)	7.0 %
				Paper (packaging)	6.1 %
				PE (packaging)	0.8 %
<b>Total plastics</b>	<b>86.1%</b>	<b>Total metals</b>	<b>0.0 %</b>	<b>Total other and packaging</b>	<b>13.9 %</b>

Estimated recycled material content: 5 % by mass.



### ■ MANUFACTURE

The Reference Product comes from sites that, in their majority, have received ISO14001 certification.



### ■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 468 km by road and 158 km by sea from our warehouse to the local point of distribution into the market in Spain.

Packaging is compliant with european directive 2004/12/EU concerning packaging and packaging waste. At their end of life, its recyclability rate is 92 % (in % of packaging weight).



### ■ INSTALLATION

For the installation of the product, only standard tools are needed.



### ■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.



### END OF LIFE

The product end-of-life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.

**• Recyclability rate:**

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 95 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 82 %
- metal materials (excluding packaging) : 0 %
- other materials (excluding packaging) : 0 %
- packaging (all types of materials) : 13 %



### ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end-of-life. It is representative of products marketed and used Spain.

For each phase, the following modelling elements were taken in account:

<b>Manufacture</b>	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
<b>Distribution</b>	Transport between the last Group distribution centre and an average delivery point in the sales area.
<b>Installation</b>	The end of life of the packaging.
<b>Use</b>	<ul style="list-style-type: none"> <li>• Product category: PSR-0003-ed1-EN-2012 02 02 - 3.3.1.2. Distribution trunking systems.</li> <li>• Use scenario: no energy consumption during the 20 years working life. This modelling duration does not constitute a minimum durability requirement.</li> <li>• Energy model: Electricity Mix ; Spain - 2002.</li> </ul>
<b>End of life</b>	The default end of life scenario maximizing the impacts.
<b>Software and database used</b>	EIME V5 and its database «CODDE-2015-04».



### SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
	Value	Unit	Value	%	Value	%	Value	%	Value	%	Value	%
Global warming	5,31E+00	kg-CO <sub>2</sub> eq.	5,11E+00	96 %	3,67E-02	< 1 %	1,10E-02	< 1 %	0,00E+00	0 %	1,49E-01	3 %
Ozone depletion	2,75E-07	kg-CFC-11 eq.	2,71E-07	99 %	7,31E-11	< 1 %	1,78E-10	< 1 %	0,00E+00	0 %	3,81E-09	1 %
Acidification of soils and water	5,96E-03	kgSO <sub>2</sub> eq.	5,09E-03	85 %	2,50E-04	4 %	4,81E-05	< 1 %	0,00E+00	0 %	5,68E-04	10 %
Water eutrophication	2,25E-03	kg-PO <sub>4</sub> <sup>3-</sup> eq.	1,50E-03	67 %	4,42E-05	2 %	5,31E-05	2 %	0,00E+00	0 %	6,47E-04	29 %
Photochemical ozone formation	9,03E-04	kg-C <sub>2</sub> H <sub>4</sub> eq.	8,84E-04	98 %	1,56E-05	2 %	3,55E-06	< 1 %	0,00E+00	0 %	3,81E-09	< 1 %
Depletion of abiotic resources - elements	7,33E-06	kgSb eq.	7,32E-06	100 %	1,45E-09	< 1 %	5,94E-10	< 1 %	0,00E+00	0 %	9,61E-09	< 1 %
Total use of primary energy	1,77E+02	MJ	1,74E+02	98 %	5,13E-01	< 1 %	1,64E-01	< 1 %	0,00E+00	0 %	2,30E+00	1 %
Net use of fresh water	3,26E-01	m <sup>3</sup>	3,26E-01	100 %	3,24E-06	< 1 %	6,56E-06	< 1 %	0,00E+00	0 %	1,31E-04	< 1 %
Depletion of abiotic resources - fossil fuels	9,47E+01	MJ	9,19E+01	97 %	5,10E-01	< 1 %	1,55E-01	< 1 %	0,00E+00	0 %	2,13E+00	2 %
Water pollution	6,94E+02	m <sup>3</sup>	6,70E+02	97 %	5,97E+00	< 1 %	1,48E+00	< 1 %	0,00E+00	0 %	1,68E+01	2 %
Air pollution	7,90E+02	m <sup>3</sup>	7,69E+02	97 %	1,85E+00	< 1 %	1,35E+00	< 1 %	0,00E+00	0 %	1,77E+01	2 %

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

The environmental impact of the system, described in this document and different of the Reference Product, can be estimated by weighting the environmental impacts of the Reference Product by the corresponding factors (see under).

Designation	Correction factor to apply to each indicators, for each life cycle steps or to the total life cycle
EUROQUINT 25 x 40 system	0.23
EUROQUINT 25 x 40 - 2 compartments system	0.25
EUROQUINT 40 x 40 system	<b>0.37</b>
EUROQUINT 40 x 60 system	<b>0.51</b>
EUROQUINT 40 x 60 - 2 compartments system	<b>0.56</b>
EUROQUINT 40 x 90 system	<b>0.71</b>
EUROQUINT 40 x 110 system	<b>0.72</b>
<b>EUROQUINT 60 x 110 system</b>	<b>1.00</b>
EUROQUINT 60 x 120 system	1.19
EUROQUINT 60 x 200 system	1.79

Registration N°: LGRP-00031-V01.01-EN	Drafting rules: «PEP-PCR-ed3-EN-2015 04 02» Supplemented by «PSR-0003-ed1-2012 02 02»
Verifier accreditation N°: VH23	Information and reference documents : <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue: 12-2015	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025:2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804 : 2012 + A1 : 2013	

