





Power	<b>18 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1250 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>120 °</b>
UGR	<b>&lt;25</b>	IK	<b>10</b>



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file



**Technical data:**

Code	SLI031020CW
Power	18 W
Nominal current	150 mA
Voltage	230 V
Energy efficiency class	G
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Useful luminous flux*	1250 lm (360°)
Luminous flux**	1250 lm (360°)
Lamp efficacy	69 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
UGR	<25
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	10
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	260X55 mm
Weight	0.6 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux