




CE

---


|                           |              |                    |                         |
|---------------------------|--------------|--------------------|-------------------------|
| Voltage                   | <b>3.7 V</b> | Colour temperature | <b>3000/4000/6000 K</b> |
| Colour of light           | <b>CCT</b>   | Beam angle         | <b>90 °</b>             |
| Degree of protection (IP) | <b>IP65</b>  |                    |                         |

---




 User manual



 Declaration of Conformity

Technical data:

|                              |   |
|------------------------------|---|
| Code                         | SLI049002   |
| Voltage                      | 3.7 V   |
| Protection class             | III   |
| Luminous flux**              | 200 lm (360°)   |
| Colour temperature           | 3000/4000/6000 K  |
| Colour of light              | CCT   |
| Beam angle                   | 90 °  |
| RA                           | 80  |
| Uniformity of color SDCM max | 5   |
| Dimmable                     | No  |
| Working temperature range    | -20/+40 °   |
| Lifespan                     | 17000 h   |
| Housing material             | PC+ABS  |
| Degree of protection (IP)    | IP65  |
| Colour                       | Black   |
| Dimension (AxBxC)            | 95x188x112 (290 with spike) mm  |
| Weight                       | 0.25 kg   |
| For use                      | Outside   |
| Assembly method              | GRUNTOWY, On the ceiling  |
| Application                  | EXT   |
| Made in                      | PRC   |
| Other                        | CCT function, Working >8-12H, charging<br>5h, , 5.5V panel, Li-ion battery, capacity<br>1800mAh |



\*applies to the LED source used. \*\*Luminaire luminous flux