


OSRAM DALI magic

Analysis- and commissioning tool for DALI installations

Please observe the safety precautions in handling the device



Operation and connection of the device only by electrically skilled persons



Indoor operation only

General information

Application

PC independent:

- Control device for switching and dimming DALI lighting systems for testing of single lights or whole illumination equipments

Only in connection with PC and software:

- Standard interface DALI ↔ USB;
 - o Central control, analysis and programming of DALI systems (e. g. reading and writing of DALI device configurations) by means of software „DALI wizard“
 - o „DALI-Spy“- Functionality for recording data flow on the DALI line by means of software „DALI wizard“
 - o Programming of OSRAM ECG with 3DIM functionality by means of software „3DIM Tool“

Technical Data

- Power supply via USB: 5 V, 60 – 350 mA, integrated overvoltage protection
- External power supply: 6 V, 1 A, Reverse polarity protected
- External supply plug: DC, EIAJ-03
- USB connection: Type B acc. IEC 61076-3-108

Temperature and lifetime

- Work ambient temperature: 0 °C...+50 °C
- Storage temperature: -20 °C...+100 °C

Housing

- Dimensions: 120 mm x 79 mm x 28 mm (W x L x H)
- Housing material: ABS
- Protection class IP20
- Weight: 143 g



DALI wizard and 3DIM Tool: Software download and manual at:

www.osram.com/lms-magic

Manufacturer address:

OSRAM GmbH

Steinerne Furt 62
D-86167 Augsburg
Germany

www.osram.com

Technical support:

www.osram.de
www.osram.com
Customer Service Center Germany
+49 (0)89-6213-60 00

OSRAM

