

APC Service Bypass Panel

Service Bypass Panels with a BBM switch for use with APC Smart-UPS® products up to 3kVA.

SBP1500RMI



Designed to work with the world's most popular network and server UPS.

SBP3000RMI



The Service Bypass Panels provide a wrap around system to allow easy maintenance of a UPS by isolating it from the critical load. The panels can be rack (2U) or wall mounted and are available with an integrated Power Distribution Unit (PDU).

- *Reliable*
- *Compact*
- *Easy to use*
- *Break Before Make (BBM) switch*

SBP3000RMHW



APC Service Bypass Panel

SBP1500RMI



SBP3000RMI



SBP3000RMHW



Standard features:

- 1 Bypass/UPS switch** allows the switching of the supply to the load between the incoming supply and the UPS, so the UPS can be isolated for maintenance.
- 2 Equipment Outlets** allowing the SBP to support multiple loads.
- 3 Output receptacle** to feed UPS input.
- 4 Input receptacle** to receive the output from the UPS.
- 5 Input receptacle** to receive the external supply (utility).
- 6 Equipment outlet circuit breaker** providing outlet protection.
- 7 Utility input terminal block access panel and hardwire knockout.**
- 8 Equipment output terminal block access panel and hardwire knockout.**

| Product feature | SBP1500RMI | SBP3000RMI | SBP3000RMHW |
|----------------------------------|---|---------------------------|------------------------|
| Input / Output ratings | | | |
| Nominal Input/Output voltage | 230V | 230V | 230V |
| Maximum total current | 10A | 16A | 16A |
| Switch characteristics | | | |
| Type / Transfer Time | Break Before Make (BBM) / 4ms max. | | |
| Connections | | | |
| External supply input connection | IEC-320 C14 | IEC-320 C20 | Hardwire |
| UPS Input / Output connections | IEC-320 C14 / C13 | IEC-320 C20 / C19 | IEC-320 C20 / C19 |
| Load connections | IEC-320 C13 (6) | IEC-320 C13 (6) + C19 (1) | Hardwire |
| Jumper cables | (2) IEC-320 C14 to C13 | (2) IEC-320 C20 to C19 | (1) IEC-320 C20 to C19 |
| Physical | | | |
| Dimensions (H x W x D) mm | 89.00 x 432.00 x 76.00 | | |
| Net weight (kg) | 2.00 | 2.09 | 2.27 |
| Conformance | | | |
| Regulatory Approvals | CE | | |
| Standard Warranty | 2 years repair or replace | | |
| Environmental Compliance | RoHS 7b Exemption, REACH: Contains No SVHCs | | |