


# PCE data sheet

article#	<b>75352-6</b>
article description	<b>CEE-switched interlocked socket 63A 5p 6h IP66/IP67</b>
description long	CEE-switched interlocked socket 63A 5p 6h IP66/IP67 housing material: PC/ABS rated current: 63A number of poles: 5 (3P+N+PE) clock-position: 6h rated voltage/frequency: 200/346V~ - 240/415V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: screw terminals wall mounting, mechanical interlock switch: ON/OFF PCE-Merz ML2-063; EN 60947-3; AC22A, 10kA cable entry: top, bottom or rear (incl. threaded blind cap) IP protection class: IP66/IP67
GTIN (EAN)	9003399068706
country of origin	AT
customs number	85366990
net weight	2.179 kg
packaging quantity	1

ETIM 7.0	EC001324
IEC-amperage	63 A
Number of poles	5
Voltage acc. EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h
Identification colour	Red
Degree of protection (IP)	IP67
Switch	Mechanical locking
Material housing	Plastic
Model	Base unit and cover
Contact material	CuZn
Surface finish contacts	Nickel-plated

wire flexible	6-25 mm <sup>2</sup>
wire solid	6-35 mm <sup>2</sup>



[www.manufacturer-safety.info](http://www.manufacturer-safety.info)