




CE

Power	<b>8 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1000 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>110 °</b>
IK	<b>6</b>	Degree of protection (IP)	<b>IP54</b>



See more on dedicated page 



 Declaration of Conformity

**Technical data:**

Code	SLI043022CW_PW
Power	8 W
Nominal current	62 mA
Voltage	230 V
Energy consumption	8 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	1000 lm (360°)
Luminous flux**	725 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	110 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC+PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	118x31 mm
Mounting hole	92 mm
Weight	0.086 kg
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*applies to the LED source used, \*\*Luminaire luminous flux