




---

|                 |                      |                    |               |
|-----------------|----------------------|--------------------|---------------|
| Power           | <b>8 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux** | <b>710 lm (360°)</b> | Colour temperature | <b>3000 K</b> |
| Light colour    | <b>WW</b>            | Beam angle         | <b>160 °</b>  |
| Base            | <b>E-14</b>          |                    |               |

---



 Declaration of Conformity

**Technical data:**

|                              |               |
|------------------------------|---------------|
| Product code                 | WOJ+14220     |
| Power                        | 8 W           |
| Nominal current              | 70 mA         |
| Voltage                      | 230 V         |
| Energy efficiency classe     | F             |
| Energy consumption           | 8 kWh/1000h   |
| Frequency                    | 50HZ Hz       |
| Power factor                 | 0.5           |
| Useful luminous flux*        | 710 lm (360°) |
| Luminous flux**              | 710 lm (360°) |
| Light efficiency             | 77 lm/W       |
| Colour temperature           | 3000 K        |
| Light colour                 | WW            |
| Beam angle                   | 160 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | No            |
| Working temperature range    | -20/+40 °     |
| Lifespan                     | 17000 h       |
| Base                         | E-14          |
| Dimension (axbxc)            | 37x107 mm     |
| Weight                       | 0.027 kg      |
| For use                      | Inside        |
| Application                  | INT           |
| Made in                      | PRC           |

