



| | | | |
|-----------------|----------------------|--------------------|---------------|
| Power | 6 W | Voltage | 230 V |
| Luminous flux** | 500 lm (360°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 45 ° |
| Base | GU10 | | |



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|---------------|
| Product code | WOJ+14092 |
| Power | 6 W |
| Nominal current | 35 mA |
| Voltage | 230 V |
| Energy efficiency classe | G |
| Energy consumption | 6 kWh/1000h |
| Frequency | 50HZ Hz |
| Power factor | 0.5 |
| Useful luminous flux* | 410 lm (90°) |
| Luminous flux** | 500 lm (360°) |
| Light efficiency | 68 lm/W |
| Luminous intensity | 800 cd |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 45 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Base | GU10 |
| Dimension (axbxc) | 50x56 mm |
| Weight | 0.05 kg |
| For use | Inside |
| Application | INT |
| Made in | PRC |

